

# **SAFETY DATA SHEETS**



## **SEALANTS & TOUCH UP PAINT**

+44 (0) 1691 663300

www.guttercrest.co.uk

info@guttercrest.co.uk

Revision Date 14/11/12 Supersedes date 26/10/05



## SAFETY DATA SHEET ARBOSIL 1090

#### SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

#### 1.1. Product identifier

Product name

ARBOSIL 1090

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Neutral cure building sealant.

#### 1.3. Details of the supplier of the safety data sheet

Supplier	Adshead Ratcliffe & Co. Ltd.
	Derby Road, Belper
	Derbyshire.
	DE56 1WJ
	Tel. (+44) 01773 826661
	Fax. (+44) 01773 821215
	sds@arbo.co.uk

#### 1.4. Emergency telephone number

(+44) 01773 826661 (office hours only)

## SECTION 2: HAZARDS IDENTIFICATION

#### 2.1. Classification of the substance or mixture

Classification (1999/45/EEC) Human health	Not classified.	
Not considered as a health hazard ur Environment	nder current legislation.	
The product is not expected to be haz 2.2. Label elements	zardous to the environment.	
Risk Phrases		
	NC	Not classified.
Safety Phrases	P13	Safety data sheet available for professional user on request.

#### 2.3. Other hazards

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

#### 3.2. Mixtures

BIS-(N-METHYLBENZAMIDO)-METHYL	ETHOXYSILANE		1 - 5%
CAS-No.: 16230-35-6	EC No.: 240-354-5		
Classification (EC 1272/2008)		Classification (67/548/EEC)	
Skin Irrit. 2 - H315		Xi;R36/37/38.	
Eye Irrit. 2 - H319			
STOT SE 3 - H335			

TITANIUMACETYLACETATE			1 - 5%
CAS-No.: 83877-91-2	EC No.: 281-161-6		
Classification (EC 1272/2008) Flam. Liq. 3 - H226		Classification (67/548/EEC) R10.	
DIOCTYLTIN DILAURATE			< 1%
CAS-No.: 3648-18-8	EC No.: 222-883-3		
Classification (EC 1272/2008) Repr. 2 - H361d STOT RE 1 - H372 Aquatic Chronic 4 - H413		Classification (67/548/EEC) T;R48/25. Repr. Cat. 3;R63. R53.	

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

#### **Composition Comments**

Polydimethylsiloxane with fillers, auxiliaries. benzamidosilane crosslinking agent.

#### SECTION 4: FIRST AID MEASURES

#### 4.1. Description of first aid measures

General information

In all cases of doubt, or if symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person.

Inhalation

If inhalation causes adverse effects, remove to fresh air.

Ingestion

Immediately rinse mouth and drink plenty of water (200-300 ml). Give milk instead of water if readily available. Get medical attention if any discomfort continues.

Skin contact

Wipe off excess material with cloth or paper. Wash the skin immediately with soap and water. Get medical attention if any discomfort continues.

Eye contact

Immediately flush with plenty of water for up to 15 minutes. Remove any contact lenses and open eyes wide apart. Get medical attention if any discomfort continues.

#### 4.2. Most important symptoms and effects, both acute and delayed

Inhalation. No specific symptoms noted. Ingestion May cause discomfort if swallowed. Skin contact No specific symptoms noted. Eye contact May cause temporary eye irritation.

#### 4.3. Indication of any immediate medical attention and special treatment needed

Treat Symptomatically.

#### SECTION 5: FIREFIGHTING MEASURES

#### 5.1. Extinguishing media

Extinguishing media Use fire-extinguishing media appropriate for surrounding materials. Unsuitable extinguishing media None known.

#### 5.2. Special hazards arising from the substance or mixture

Hazardous combustion products

Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapours.

#### Unusual Fire & Explosion Hazards No unusual fire or explosion hazards noted. Specific hazards In case of fire, toxic gases may be formed.

#### 5.3. Advice for firefighters

Special Fire Fighting Procedures Avoid breathing fire vapours. Keep up-wind to avoid fumes. Protective equipment for fire-fighters Wear self contained breathing apparatus.

#### SECTION 6: ACCIDENTAL RELEASE MEASURES

#### 6.1. Personal precautions, protective equipment and emergency procedures

Wear appropriate protective clothing. Follow precautions for safe handling described in this safety data sheet.

#### 6.2. Environmental precautions

Avoid discharge into drains, water courses or onto the ground.

#### 6.3. Methods and material for containment and cleaning up

Shovel into dry containers. Cover and move the containers. Flush the area with water. Wash thoroughly after dealing with a spillage.

#### 6.4. Reference to other sections

For personal protection, see section 8. See section 11 for additional information on health hazards. For waste disposal, see section 13.

#### SECTION 7: HANDLING AND STORAGE

#### 7.1. Precautions for safe handling

Avoid spilling, skin and eye contact. Observe good chemical hygiene practices.

#### 7.2. Conditions for safe storage, including any incompatibilities

Store in tightly closed original container in a dry, cool and well-ventilated place.

Storage Class

## Unspecified storage.

#### 7.3. Specific end use(s)

The identified uses for this product are detailed in Section 1.2. Usage Description Gunnable sealant.

### SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

#### 8.1. Control parameters

Name	STD	TWA	- 8 Hrs	STEL	- 15 Min	Notes
DIOCTYLTIN DILAURATE	WEL		0.1 mg/m3		0.2 mg/m3	as Sn

WEL = Workplace Exposure Limit.

Ingredient Comments No DNEL or PNEC values available.

#### 8.2. Exposure controls

Protective equipment



Engineering measures No particular ventilation requirements. Respiratory equipment Not normally required. Hand protection Use suitable protective gloves if risk of skin contact.

#### Eye protection Not generally required. Hygiene measures DO NOT SMOKE IN WORK AREA! Wash hands at the end of each work shift and before eating, smoking and using the toilet. Wash promptly if skin becomes contaminated. Promptly remove any clothing that becomes contaminated. When using do not eat, drink or smoke.

#### SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

#### 9.1. Information on basic physical and chemical properties

Appearance	Uncured -paste. Cured - rubber.
Colour	Misc. colours.
Odour	Slight odour.
Solubility	Insoluble in water
Initial boiling point and boiling range	Not applicable.
Relative density	1.18 - 1.195 @ 20"C
Vapour density (air=1)	Not applicable.
Vapour pressure	Not applicable.
Evaporation rate	Not applicable.
pH-Value, Conc. Solution	Not applicable.
Viscosity	5, 000 - 7, 000 Ps @ 20°C
Solubility Value (G/100G H2O@20°C)	Not applicable.
Odour Threshold, Lower	Not applicable.
Odour Threshold, Upper	Not applicable.
Flash point	Not applicable.
Auto Ignition Temperature (°C)	450 (as paste)
Flammability Limit - Lower(%)	Not applicable.
Flammability Limit - Upper(%)	Not applicable.
Partition Coefficient	Not applicable.
(N-Octanol/Water)	
Explosive properties	Not applicable.
Oxidising properties	Not applicable.
9.2. Other information	

None.

#### SECTION 10: STABILITY AND REACTIVITY

#### 10.1. Reactivity

No specific reactivity hazards associated with this product.

#### 10.2. Chemical stability

Stable under normal temperature conditions and recommended use.

#### 10.3. Possibility of hazardous reactions

Not applicable. Hazardous Polymerisation Will not polymerise. **10.4. Conditions to avoid** 

Avoid excessive heat for prolonged periods of time. **10.5.** Incompatible materials

Materials To Avoid No specific, or groups of materials are likely to react to produce a hazardous situation.

#### 10.6. Hazardous decomposition products

None under normal conditions. Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapours.

SECTION 11: TOXICOLOGICAL INFORMATION

#### 11.1. Information on toxicological effects

Not determined

#### **ARBOSIL 1090**

#### Toxic Dose 2 - LD 50 Toxic Conc. - LC 50

Not determined

Not determined

Toxicological information

The product has been assessed following the conventional method of the Dangerous Preparations Directive 1999/45/EC and classified for toxicological hazards accordingly.

#### Acute toxicity:

Based on available data the classification criteria are not met.

#### Skin Corrosion/Irritation:

Based on available data the classification criteria are not met.

#### Serious eye damage/irritation:

Based on available data the classification criteria are not met.

<u>Respiratory or skin sensitisation:</u> Based on available data the classification criteria are not met.

#### <u>Germ cell mutagenicity:</u> Does not contain any substances known to be mutagenic.

<u>Carcinogenicity:</u> Does not contain any substances known to be carcinogenic.

<u>Reproductive Toxicity:</u> Based on available data the classification criteria are not met.

Inhalation No specific health warnings noted.

Ingestion No harmful effects expected in amounts likely to be ingested by accident.

Skin contact Skin irritation is not anticipated when used normally. Eye contact May cause temporary eye irritation. Will not injure eye tissue.

#### SECTION 12: ECOLOGICAL INFORMATION

#### Ecotoxicity

Not regarded as dangerous for the environment. The product has been assessed following the conventional method of the Dangerous Preparations Directive 1999/45/ EC and classified for ecotoxicological hazards accordingly.

#### 12.1. Toxicity

LC 50, 96 Hrs, Fish mg/l	Not determined
EC 50, 48 Hrs, Daphnia, mg/l	Not determined
IC 50, 72 Hrs, Algae, mg/l	Not determined

#### 12.2. Persistence and degradability

Degradability Silicone content: biologically not degradable.

#### 12.3. Bioaccumulative potential

Bioaccumulative potential No data available on bioaccumulation. Partition coefficient Not applicable.

#### 12.4. Mobility in soil

Mobility: The product is insoluble in water.

#### 12.5. Results of PBT and vPvB assessment

This product does not contain any PBT or vPvB substances.

#### 12.6. Other adverse effects

None known.

#### SECTION 13: DISPOSAL CONSIDERATIONS

General information

When handling waste, consideration should be made to the safety precautions applying to handling of the product.

#### 13.1. Waste treatment methods

Dispose of waste and residues in accordance with local authority requirements. Waste Class Recommended EWC Code 08 04 10

#### **SECTION 14: TRANSPORT INFORMATION**

General

The product is not covered by international regulation on the transport of dangerous goods (IMDG, IATA, ADR/RID).

#### 14.1. UN number

No information required.

#### 14.2. UN proper shipping name

No information required.

#### 14.3. Transport hazard class(es)

No information required.

#### 14.4. Packing group

No information required.

#### 14.5. Environmental hazards

Environmentally Hazardous Substance/Marine Pollutant No.

#### 14.6. Special precautions for user

No information required.

#### 14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

No information required.

#### SECTION 15: REGULATORY INFORMATION

#### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Uk Regulatory References Chemicals (Hazard Information & Packaging) Regulations. Statutory Instruments Control of Substances Hazardous to Health. Guidance Notes Workplace Exposure Limits EH40. EU Legislation Dangerous Substance Directive 67/548/EEC. Dangerous Preparations Directive 1999/45/EC. Regulation (EC) 1907/2006 REACH. Regulation (EC) 1272/2008 CLP. **15.2. Chemical Safety Assessment** 

No chemical safety assessment has been carried out.

#### **SECTION 16: OTHER INFORMATION**

Revision Comments General review New format as required by REACH Annex II

#### **ARBOSIL 1090**

Revision Date	14/11/12
Supersedes date	26/10/05
SDS No.	10165
Risk Phrases In Full	
R10	Flammable.
R36/37/38	Irritating to eyes, respiratory system and skin.
R53	May cause long-term adverse effects in the aquatic environment.
NC	Not classified.
R63	Possible risk of harm to the unborn child.
R48/25	Toxic: danger of serious damage to health by prolonged exposure if swallowed.
Hazard Statements In Full	
H372	Causes damage to organs << Organs>> through prolonged or repeated exposure.
H319	Causes serious eye irritation.
H315	Causes skin irritation.
H226	Flammable liquid and vapour.
H413	May cause long lasting harmful effects to aquatic life.
H335	May cause respiratory irritation.
H361d	Suspected of damaging the unborn child.

Disclaimer

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in a process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.



## SAFETY DATA SHEET **ARBOSEAL TAPE**

#### SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

#### 1.1. Product identifier

Product name	ARBOSEAL TAPE
Synonyms, Trade Names	Arboseal GZ., 03-SV., Butyl 88., G

Arboseal GZ., 03-SV., Butyl 88. , Glazing tape., Lap tape.

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses

Compression joints in cladding and roofing. Lap joints in guttering. Glazing applications.

#### 1.3. Details of the supplier of the safety data sheet

Supplier

Adshead Ratcliffe & Co. Ltd. Derby Road, Belper Derbyshire. **DE56 1WJ** Tel. (+44) 01773 826661 Fax. (+44) 01773 821215 sds@arbo.co.uk

#### 1.4. Emergency telephone number

(+44) 01773 826661 (office hours only)

#### **SECTION 2: HAZARDS IDENTIFICATION**

#### 2.1. Classification of the substance or mixture

Classification (1999/45/EEC) Not classified.

Human health

Not considered as a health hazard under current legislation.

Environment

Not regarded as an environmental hazard under current legislation.

#### 2.2. Label elements

#### 2.3. Other hazards

#### SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

#### 3.2. Mixtures

**Composition Comments** 

Butyl rubber, polyisobutene / polyisobutylene blends, with fillers, auxiliaries.

#### **SECTION 4: FIRST AID MEASURES**

#### 4.1. Description of first aid measures

General information

In all cases of doubt, or if symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person.

Inhalation

Unlikely route of exposure.

Ingestion

Unlikely, but should this occur seek medical advice.

Skin contact

Wipe off excess material with cloth or paper. Wash the skin immediately with soap and water. Get medical attention if any discomfort continues.

Eye contact

Immediately flush with plenty of water for up to 15 minutes. Remove any contact lenses and open eyes wide apart. Get medical attention if any discomfort continues.

#### 4.2. Most important symptoms and effects, both acute and delayed

## **ARBOSEAL TAPE**

Inhalation. No specific symptoms noted. Ingestion May cause discomfort if swallowed. Skin contact No specific symptoms noted. Eye contact May cause temporary eye irritation.

#### 4.3. Indication of any immediate medical attention and special treatment needed

Treat Symptomatically.

#### SECTION 5: FIREFIGHTING MEASURES

#### 5.1. Extinguishing media

Extinguishing media Use fire-extinguishing media appropriate for surrounding materials. Unsuitable extinguishing media None known. 5.2. Special hazards arising from the substance or mixture Hazardous combustion products

Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapours. Unusual Fire & Explosion Hazards No unusual fire or explosion hazards noted. Specific hazards In case of fire, toxic gases may be formed. **5.3. Advice for firefighters** 

Special Fire Fighting Procedures Avoid breathing fire vapours. Keep up-wind to avoid fumes. Protective equipment for fire-fighters Wear self contained breathing apparatus.

#### SECTION 6: ACCIDENTAL RELEASE MEASURES

#### 6.1. Personal precautions, protective equipment and emergency procedures

Wear appropriate protective clothing. Follow precautions for safe handling described in this safety data sheet.

#### 6.2. Environmental precautions

Avoid discharge into drains, water courses or onto the ground.

#### 6.3. Methods and material for containment and cleaning up

#### Non-hazardous substance. Transfer to a container for disposal.

#### 6.4. Reference to other sections

For personal protection, see section 8. See section 11 for additional information on health hazards. For waste disposal, see section 13.

SECTION 7: HANDLING AND STORAGE

#### 7.1. Precautions for safe handling

Observe good chemical hygiene practices.

#### 7.2. Conditions for safe storage, including any incompatibilities

Store in closed containers in a cool, dry place.

Storage Class

Unspecified storage.

#### 7.3. Specific end use(s)

The identified uses for this product are detailed in Section 1.2.

#### SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

#### 8.1. Control parameters

## **ARBOSEAL TAPE**

#### 8.2. Exposure controls

Protective equipment



Engineering measures No particular ventilation requirements. Respiratory equipment Not normally required. Hand protection For prolonged or repeated skin contact use suitable protective gloves. Eye protection Not generally required. Hygiene measures Wash hands at the end of each work shift and before eating, smoking and using the toilet. When using do not eat, drink or smoke.

#### SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

#### 9.1. Information on basic physical and chemical properties

Appearance	Round and flat section tacky tape.
Colour	Black. White. Teak.
Odour	Odourless.
Solubility	Insoluble in water
Relative density	1.22 - 1.60 @ 20"C

#### 9.2. Other information

### SECTION 10: STABILITY AND REACTIVITY

#### 10.1. Reactivity

No specific reactivity hazards associated with this product.

#### 10.2. Chemical stability

Stable under normal temperature conditions and recommended use.

#### 10.3. Possibility of hazardous reactions

Not applicable. Hazardous Polymerisation Will not polymerise.

#### 10.4. Conditions to avoid

Avoid excessive heat for prolonged periods of time.

#### 10.5. Incompatible materials

Materials To Avoid

No specific, or groups of materials are likely to react to produce a hazardous situation.

#### 10.6. Hazardous decomposition products

None under normal conditions. Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapours.

### SECTION 11: TOXICOLOGICAL INFORMATION

#### 11.1. Information on toxicological effects

Toxic Dose 1 - LD 50	Not determined
Toxic Dose 2 - LD 50	Not determined
Toxic Conc LC 50	Not determined

## **ARBOSEAL TAPE**

Ingestion No harmful effects expected in amounts likely to be ingested by accident.

Skin contact Prolonged contact may cause dryness of the skin. Eye contact No specific health warnings noted.

#### SECTION 12: ECOLOGICAL INFORMATION

#### Ecotoxicity

Not regarded as dangerous for the environment.

#### 12.1. Toxicity

LC 50, 96 Hrs, Fish mg/l	Not determined
EC 50, 48 Hrs, Daphnia, mg/l	Not determined
IC 50, 72 Hrs, Algae, mg/l	Not determined

#### 12.2. Persistence and degradability

Degradability There are no data on the degradability of this product.

#### 12.3. Bioaccumulative potential

Bioaccumulative potential No data available on bioaccumulation.

#### 12.4. Mobility in soil

Mobility: The product is insoluble in water.

#### 12.5. Results of PBT and vPvB assessment

#### 12.6. Other adverse effects

#### SECTION 13: DISPOSAL CONSIDERATIONS

General information

When handling waste, consideration should be made to the safety precautions applying to handling of the product.

#### 13.1. Waste treatment methods

Dispose of waste and residues in accordance with local authority requirements.

Waste Class

Recommended EWC Code 08 04 10

#### SECTION 14: TRANSPORT INFORMATION

General

The product is not covered by international regulation on the transport of dangerous goods (IMDG, IATA, ADR/RID).

#### 14.1. UN number

#### 14.2. UN proper shipping name

#### 14.3. Transport hazard class(es)

#### 14.4. Packing group

#### 14.5. Environmental hazards

#### 14.6. Special precautions for user

#### 14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

#### SECTION 15: REGULATORY INFORMATION

#### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Uk Regulatory References Chemicals (Hazard Information & Packaging) Regulations. Statutory Instruments Control of Substances Hazardous to Health. Guidance Notes Workplace Exposure Limits EH40. EU Legislation Dangerous Substance Directive 67/548/EEC. Dangerous Preparations Directive 1999/45/EC. Regulation (EC) 1907/2006 REACH. Regulation (EC) 1272/2008 CLP. **15.2. Chemical Safety Assessment** 

#### SECTION 16: OTHER INFORMATION

General information

This document is outside the scope of Article 31 of REACH and is therefore not compiled in accordance with Annex II.

Revision Comments	
General review	
Revision Date	21/11/12
Supersedes date	14/11/05
SDS No.	10270

Disclaimer

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in a process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.



Page 1/10

## **TOUCH UP PAINT**

Safety data sheet

Printing date 15.02.2018

according to 1907/2006/EC, Article 31

Revision: 29.01.2018

SECTION 1: Identification of the substance/mixture and of the company/undertaking

· 1.1 Product identifier For professional use only

· Trade name: QAD Enamel Colours

· 1.2 Relevant identified uses of the substance or mixture and uses advised against Surface Coating

· Application of the substance / the mixture Surface Coating

 $\cdot$  1.3 Details of the supplier of the safety data sheet

• Supplier: HMG PAINTS LIMITED RIVERSIDE WORKS, COLLYHURST ROAD, MANCHESTER. M40 7RU UNITED KINGDOM TEL: +44 (0)161 205 7631 EMAIL: sales@hmgpaint.com

• Further information obtainable from: sales@hmgpaint.com • 1.4 Emergency telephone number: +44 (0)161 205 7631 (Business hours)

**SECTION 2: Hazards identification** 

· 2.1 Classification of the substance or mixture

· Classification according to Regulation (EC) No 1272/2008

Flam. Liq. 3 H226 Flammable liquid and vapour.

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2 H319 Causes serious eye irritation.

STOT SE 3 H335 May cause respiratory irritation.

STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.

· 2.2 Label elements

· Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

• Hazard pictograms



· Signal word Warning

• *Hazard-determining components of labelling: Xylene (mix)* 

· Hazard statements

H226 Flammable liquid and vapour.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H335 May cause respiratory irritation.

H373 May cause damage to organs through prolonged or repeated exposure.

• Precautionary statements P210 Keep of

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

(Contd. on page 2)

<sup>-</sup> GB

Printing date 15.02.2018

Revision: 29.01.2018

Trade name: QAD Enamel Colours

	(Contd. of page 1)
P241	Use explosion-proof electrical/ventilating/lighting equipment.
P303+P361+P353	3 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
P305+P351+P338	3 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P405	Store locked up.
P501	Dispose of contents/container in accordance with local/regional/national/international regulations.
· Additional inform	ation:
Contains 2-butano	ne oxime, methyl methacrylate. May produce an allergic reaction.

· 2.3 Other hazards

· Results of PBT and vPvB assessment

• *PBT:* Not applicable.

• **vPvB:** Not applicable.

## **SECTION 3: Composition/information on ingredients**

· 3.2 Chemical characterisation: Mixtures

• Description: Mixture of substances listed below with nonhazardous additions.

· Dangerous component	ts:	
EINECS: 215-535-7	Kylene (mix) Flam. Liq. 3, H226; I STOT RE 2, H373; Asp. Tox. 1, H304; I Acute Fox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335	25-50%
EINECS: 292-694-9 🧹	Kylene (mixed isomers) Flam. Liq. 3, H226; I Asp. Tox. 1, H304; I Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315	10-25%
CAS: 108-65-6 2- EINECS: 203-603-9	P-methoxy-1-methylethyl acetate Flam. Liq. 3, H226	2.5-10%
EINECS: 202-849-4 🤇	thylbenzene Flam. Liq. 2, H225; 🚸 STOT RE 2, H373; Asp. Tox. 1, H304; 🕚 Acute Tox. 4, H332	2.5-10%
EINECS: 202-851-5	tyrene monomer Flam. Liq. 3, H226; & Repr. 2, H361d; STOT RE 1, H372; Asp. Tox. 1, H304; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT E 3, H335; Aquatic Chronic 3, H412	<i>≤</i> 2.5%
EINECS: 203-625-9	Toluene Flam. Liq. 2, H225; 🚸 Repr. 2, H361d; STOT RE 2, H373; Asp. Tox. 1, H304; 🔿 Skin Irrit. 2, H315; STOT SE 3, H336; Aquatic Chronic 3, H412	≤ 2.5%
EINECS: 202-496-6 🔇	2-butanone oxime	≤ 2.5%
EINECS: 201-297-1 🯹	nethyl methacrylate Flam. Liq. 2, H225; 🚸 Skin Irrit. 2, H315; Skin Sens. 1, H317; STOT SE , H335	<i>≤</i> 2.5%

• Additional information: For the wording of the listed hazard phrases refer to section 16.

## **SECTION 4: First aid measures**

• 4.1 Description of first aid measures

· After inhalation:

In case of unconsciousness place patient stably in side position for transportation. Supply fresh air; consult doctor in case of complaints.

(Contd. on page 3)

<sup>-</sup> GB

Printing date 15.02.2018

Revision: 29.01.2018

(Contd. of page 2)

Trade name: QAD Enamel Colours

- After skin contact:
- *Immediately wash with water and soap and rinse thoroughly. Remove contaminated clothing. After eye contact:*
- *Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor. After swallowing:*
- Do not induce vomiting; call for medical help immediately and show safety datasheet or label.
- 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- $\cdot$  4.3 Indication of any immediate medical attention and special treatment needed Treat symptomatically.

## **SECTION 5: Firefighting measures**

- · 5.1 Extinguishing media
- · Suitable extinguishing agents:
- CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- · For safety reasons unsuitable extinguishing agents: Water with full jet
- 5.2 Special hazards arising from the substance or mixture No further relevant information available.
- · 5.3 Advice for firefighters
- · Protective equipment: Put on breathing apparatus

## **SECTION 6: Accidental release measures**

- 6.1 Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away.
- 6.2 Environmental precautions: Prevent seepage into sewage system, workpits and cellars. Do not allow to enter sewers/ surface or ground water.
- 6.3 Methods and material for containment and cleaning up: Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose contaminated material as waste according to item 13. Ensure adequate ventilation.
- 6.4 Reference to other sections
  See Section 7 for information on safe handling.
  See Section 8 for information on personal protection equipment.
  See Section 13 for disposal information.

## **SECTION 7: Handling and storage**

- 7.1 Precautions for safe handling Keep receptacles tightly sealed.
- *Information about fire and explosion protection: Keep ignition sources away - Do not smoke. Protect against electrostatic charges.*
- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles:

Materials such as cleaning rags, paper wipes and protective clothing, which are contaminated with the product may spontaneously self-ignite some hours later. To avoid the risk of fires, all contaminated materials should be [stored in purpose-built containers or in metal containers with tight-fitting self-closing lids.] or [laid out flat in a single layer to dry] or [placed in a metal container soaked with water] or [washed out well with warm soapy water before disposal.] Contaminated materials should be removed from the workplace at the end of each working day and stored outside.

- · Information about storage in one common storage facility: Not required.
- $\cdot$  Further information about storage conditions:

*Keep receptacle tightly sealed and in a well-ventilated place. Keep away from heat.* 

(Contd. on page 4)

GB

Revision: 29.01.2018

Trade name: QAD Enamel Colours

Printing date 15.02.2018

• 7.3 Specific end use(s) No further relevant information available.

## SECTION 8: Exposure controls/personal protection

• Additional information about design of technical facilities: No further data; see item 7.

Ingredient	ts with l	limit values that require monitoring at the workplace:	
1330-20-7	Xylene	e (mix)	
Long		value: 441 mg/m³, 100 ppm value: 220 mg/m³, 50 ppm	
108-65-62	<b>?-meth</b> o	pxy-1-methylethyl acetate	
		value: 548 mg/m³, 100 ppm value: 274 mg/m³, 50 ppm	
100-41-4 е	thylben	nzene	
		value: 552 mg/m³, 125 ppm value: 441 mg/m³, 100 ppm	
DNELs			
1330-20-7	Xylene	e (mix)	
Dermal	DNEL	108 mg/day (Con)	
		180 mg/day (Ind)	
Inhalative	DNEL	14.8 mg/m <sup>3</sup> (Con)	
		77 mg/m <sup>3</sup> (Ind)	
108-65-62	e-metho	pxy-1-methylethyl acetate	
Oral	DNEL	36 mg/day (Con)	
Dermal	DNEL	320 mg/day (Con)	
		796 mg/day (Ind)	
Inhalative	DNEL	33 mg/m <sup>3</sup> (Con)	
		275 mg/m <sup>3</sup> (Ind)	
108-88-3 1	Toluene	2	
Oral	DNEL	8.13 mg/day (Con)	
Dermal	DNEL	226 mg/day (Con)	
		384 mg/day (Ind)	
Inhalative	DNEL	$56.5 mg/m^3 (Con)$	
		192 mg/m <sup>3</sup> (Ind)	
100-42-5 s	tyrene	monomer	
Oral	DNEL	2.1 mg/day (Con)	
Dermal	DNEL	343 mg/day (Con)	
		406 mg/day (Wor)	
Inhalative	DNEL	$10.2 mg/m^3 (Con)$	
		85 mg/m <sup>3</sup> (Wor)	
96-29-7 2-	butano	ne oxime	
Dermal	DNEL	0.78 mg/day (Con)	
		1.3 mg/day (Ind)	
Inhalative	DNEL	$2.7 mg/m^3$ (Con)	

(Contd. of page 3)

Printing date 15.02.2018

Revision: 29.01.2018

## Trade name: QAD Enamel Colours

		9 mg/m <sup>3</sup> (Ind) (Contd	. of page
80-62-6 m	ethvl m	ethacrylate	
Dermal		8.2 mg/day (Con)	
Derman	DIILL	13.67 mg/day (Ind)	
Inhalativa		74.3 mg/m <sup>3</sup> (Con)	
ттишиче	DIVLL	210 mg/m <sup>3</sup> (Ind)	
PNECs			
	330-20-	7 Xylene mixed isomers	
- Fresh wa			
- Marine w			
		use; 0.327 mg/l	
- STP; 6.5			
		vater); 12.46 mg/kg	
		ewater); 12.46 mg/kg	
- Soil; 2.31			
-		iological limit values:	
1330-20-7			
		mol creatinine	
	edium: ı		
		time: post shift :: methyl hippuric acid	
		ation: The lists valid during the making were used as basis.	
Wash hand Store prote	ls before ective cl	ye all soiled and contaminated clothing e breaks and at the end of work. othing separately. e the eyes and skin.	
Respirator	y protec	tion: When spraying the product, use a respiratory protective device.	
Protection			
when skin usage time		re may occur, advice should be sought from the glove supplier on appropriate t s product.	ypes ai
MIN I	Protect	ive gloves	
and varies	ion of th from n of the g	e suitable gloves does not only depend on the material, but also on further marks on nanufacturer to manufacturer. As the product is a preparation of several substa love material can not be calculated in advance and has therefore to be checked pr	nces, t
Penetratio	n time d	<b>f glove material</b> rough time has to be found out by the manufacturer of the protective gloves and a	has to
Eye protec	tion:		
	Tightly	sealed goggles	

(Contd. on page 6)

GB

Printing date 15.02.2018

Revision: 29.01.2018

Trade name: QAD Enamel Colours

(Contd. of page 5)

SECTION 9: Physical and chemic	cal properties
9.1 Information on basic physical and ch General Information Appearance:	hemical properties
Form:	Liquid
Colour:	According to product specification
Odour:	Characteristic
Odour threshold:	Not determined.
pH-value:	Not determined.
Change in condition Melting point/freezing point: Initial boiling point and boiling range:	Undetermined. 136°C
Flash point:	24°C
Flammability (solid, gas):	Not applicable.
Ignition temperature:	> 432 °C
Decomposition temperature:	Not determined.
Auto-ignition temperature:	Product is not selfigniting.
Explosive properties:	Product is not explosive. However, formation of explosive air vapour mixtures are possible.
Explosion limits:	
Lower:	1.0 Vol %
Upper:	7.0 Vol %
Vapour pressure at 20°C:	6.7 hPa
Density at 20°C:	$0.976 \ g/cm^3$
Relative density	Not determined.
Vapour density	Not determined.
Evaporation rate	Not determined.
Solubility in / Miscibility with	
water:	NOT MISCIBLE
Partition coefficient: n-octanol/water:	Not determined.
Viscosity:	200 P
Dynamic at 20°C:	200 mPas
Kinematic:	Not determined.
Solvent content:	
Organic solvents:	37.4 %
Solids content:	45.2 %
9.2 Other information	No further relevant information available.

## **SECTION 10: Stability and reactivity**

· 10.1 Reactivity No further relevant information available.

· 10.2 Chemical stability

- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- 10.3 Possibility of hazardous reactions No dangerous reactions known.
- 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.

(Contd. on page 7) GB

Printing date 15.02.2018

Revision: 29.01.2018

(Contd. of page 6)

Trade name: QAD Enamel Colours

· 10.6 Hazardous decomposition products:

No dangerous decomposition products when stored and handled correctly

## SECTION 11: Toxicological information

#### · 11.1 Information on toxicological effects

• Acute toxicity Based on available data, the classification criteria are not met.

	•	want for classification:
1330-20-7	Xylene (m	uix)
Oral	LD50	5,000 mg/kg (Rat)
Dermal	LD50	2,000 mg/kg (rbt)
Inhalative	LC50/4 h	4,300 mg/l (Rat)
100-41-4 е	ethylbenzer	ne
Oral	LD50	3,500 mg/kg (rat)
Dermal	LD50	17,800 mg/kg (rbt)
108-65-62	e-methoxy-	1-methylethyl acetate
Oral	LD50	>5,000 mg/kg (rat)
Dermal	LD50	5,000 mg/kg (Rat)
Inhalative	LC50/4 h	>10.8 mg/l (Rat)
108-88-3 1	Foluene	
Oral	LD50	5,580 mg/kg (Rat)
Dermal	LD50	5,000 mg/kg (Rab)
Inhalative	LC50/4 h	20 mg/l (Rat)
100-42-5 s	tyrene mo	nomer
Oral	LD50	5,000 mg/kg (Rat)
Dermal	LD50	>2,000 mg/kg (Rat)
Inhalative	LC50/4 h	11.8 mg/l (Rat)
96-29-7 2-	butanone	oxime
Oral	LD50	2,326 mg/kg (rat)
Dermal	LD50	1,000 mg/kg (Rab)
		200-2,000 mg/kg (rat)
Inhalative	LC50/4 h	>4.8 mg/l (rat)
80-62-6 m	ethyl meth	acrylate
Oral	LD50	7,900 mg/kg (Rat)
Inhalative	LC50/4 h	29.8 mg/l (Rat)
CMR effect Germ cell Carcinoge Reproduct STOT-sing	sion/irrita in irritation e damage/ vious eye ir y or skin s cts (carcino mutagenic nicity Bass vive toxicity gle exposu e respirator	tion irritation irritation. ensitisation Based on available data, the classification criteria are not met. ogenity, mutagenicity and toxicity for reproduction) eity Based on available data, the classification criteria are not met. ed on available data, the classification criteria are not met. w Based on available data, the classification criteria are not met. w Based on available data, the classification criteria are not met. w Based on available data, the classification criteria are not met. w Fased on available data, the classification criteria are not met. w Fased on available data, the classification criteria are not met. w Fased on available data, the classification criteria are not met. w Fased on available data, the classification criteria are not met. w Fased on available data, the classification criteria are not met. w Fased on available data, the classification criteria are not met. w Fased on available data, the classification criteria are not met.
		o organs through prolonged or repeated exposure.
-	Ũ	(Contd. on pa

(Contd. on page 8)

<sup>-</sup> GB

Printing date 15.02.2018

Revision: 29.01.2018

Trade name: QAD Enamel Colours

(Contd. of page 7)

· Aspiration hazard Based on available data, the classification criteria are not met.

## **SECTION 12: Ecological information**

- · 12.1 Toxicity
- Aquatic toxicity: No further relevant information available.
- · 12.2 Persistence and degradability No further relevant information available.
- 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- Additional ecological information:
- · General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water Do not allow product to reach ground water, water course or sewage system. Danger to drinking water if even small quantities leak into the ground.

- · 12.5 Results of PBT and vPvB assessment
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

· 12.6 Other adverse effects No further relevant information available.

### **SECTION 13: Disposal considerations**

#### · 13.1 Waste treatment methods

· Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- Uncleaned packaging:
- *Recommendation: Disposal must be made according to official regulations.*

• 14.1 UN-Number • ADR, IMDG, IATA	UN1263	
· 14.2 UN proper shipping name		
ADR	1263 PAINT	
· IMDG, IATA	PAINT	
· 14.3 Transport hazard class(es)		
ADR, IMDG, IATA		
· Class	3 Flammable liquids.	
Label	3	
14.4 Packing group		
ADR, IMDG, IATA	111	
14.5 Environmental hazards:		
Marine pollutant:	No	
1465	Warning: Flammable liquids.	
14.0 Special precautions for user		
• 14.6 Special precautions for user • Danger code (Kemler):	30	

Printing date 15.02.2018

Revision: 29.01.2018

Trade name: QAD Enamel Colours

	(Contd. of page
Stowage Category	A
· 14.7 Transport in bulk according to Anne	ex II of
Marpol and the IBC Code	Not applicable.
· Transport/Additional information:	
· ADR	
· Limited quantities (LQ)	5L
$\cdot$ Excepted quantities (EQ)	Code: El
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 1000 ml
· Transport category	3
• Tunnel restriction code	D/E
· IMDG	
· Limited quantities (LQ)	5L
$\cdot$ Excepted quantities ( $\widetilde{EQ}$ )	Code: El
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 1000 ml
· UN "Model Regulation":	UN 1263 PAINT, 3, III

## **SECTION 15: Regulatory information**

· 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P5c FLAMMABLE LIQUIDS
- $\cdot$  Qualifying quantity (tonnes) for the application of lower-tier requirements 5.000 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 50.000 t
- · REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3, 48

· National regulations:

· Technical instructions (air):

Class	Share in %		
Ι	0.2		
NK	37.4		

· Waterhazard class: Water hazard class 2 (Self-assessment): hazardous for water.

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

## **SECTION 16: Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

#### · Relevant phrases

H225 Highly flammable liquid and vapour.

- H226 Flammable liquid and vapour.
- H304 May be fatal if swallowed and enters airways.
- H312 Harmful in contact with skin.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H318 Causes serious eye damage.
- H319 Causes serious eye irritation.
- H332 Harmful if inhaled.
- H335 May cause respiratory irritation.
- H336 May cause drowsiness or dizziness.

(Contd. on page 10)

Printing date 15.02.2018

Revision: 29.01.2018

#### Trade name: QAD Enamel Colours

(Contd. of page 9) H351 Suspected of causing cancer. H361d Suspected of damaging the unborn child. H372 Causes damage to organs through prolonged or repeated exposure. H373 May cause damage to organs through prolonged or repeated exposure. H412 Harmful to aquatic life with long lasting effects. · Department issuing SDS: Product safety department: LABORATORY · Contact: Health & Safety Officer · Abbreviations and acronyms: RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail) ICAO: International Civil Aviation Organisation ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods IATA: International Air Transport Association GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) DNEL: Derived No-Effect Level (REACH) PNEC: Predicted No-Effect Concentration (REACH) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Flam. Liq. 2: Flammable liquids - Category 2 Flam. Liq. 3: Flammable liquids - Category 3 Acute Tox. 4: Acute toxicity - Category 4 Skin Irrit. 2: Skin corrosion/irritation - Category 2 Eye Dam. 1: Serious eye damage/eye irritation - Category 1 Eye Irrit. 2: Serious eye damage/eye irritation – Category 2 Skin Sens. 1: Skin sensitisation - Category 1 Carc. 2: Carcinogenicity – Category 2 Repr. 2: Reproductive toxicity – Category 2 STOT SE 3: Specific target organ toxicity (single exposure) – Category 3 STOT RE 1: Specific target organ toxicity (repeated exposure) - Category 1 STOT RE 2: Specific target organ toxicity (repeated exposure) - Category 2 Asp. Tox. 1: Aspiration hazard - Category 1 Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard - Category 3