



Project: _____

Customer: _____ Reference: _____

Name: _____ Email: _____

A - WALL THICKNESS:		(See note 1)
B - FRONT COPING HEIGHT:		(65mm standard)
C - BACK COPING HEIGHT:		(55mm standard)
D - FALL FRONT TO BACK:		(10mm fall standard)
E - WALL TO COPING BRKT CLERANCE:		(Miniumum 15mm)
F - WALL TO FRONT DRIP CLEARANCE:		(10mm standard)
G - PAINT COLOUR OR MILL FINISH:		(RAL/BS)

1. **WARNING** WALLS SHOULD ONLY BE MEASURED AFTER ALL SITE FINISHES HAVE BEEN APPLIED, i.e. RENDERING/CLADDING ETC. AND AT REGULAR INTERVALS TO ENSURE CORRECT SIZING.
2. **BRACKETS** - WILL HAVE FIXING HOLES 60MM FROM THE INSIDE EDGE OF THE BRACKET. FOR NON-STANDARD FIXING POSITION OR SPECIAL PURPOSE BRACKETS i.e. CANTILEVER etc. PLEASE CONTACT GUTTERCREST TECHNICAL DEPARTMENT.
3. **COPING SYSTEM IS SUPPLIED WITH STANDARD BRACKETS.**

GUTTERCREST LTD ACCEPT NO LIABILITY. IT IS THE END USER'S RESPONSIBILITY TO ENSURE THE PRODUCT, FIXINGS AND FIXING BACKGROUNDS ARE SUITABLE AND FIT FOR PURPOSE.

Signature: _____ Date: _____